

SCKCL03-N(75Ω) High Precision Calibration Kit

(DC - 3GHz / N-type)

Key Features

- Frequency Range: DC to 3GHz
- VSWR : <1.04
- Calibration standards to perform full two-port calibration
- Adapters and torque wrench included
- >500 times Cycles



Overview

Saluki's SCKCL03-N(75Ω) mechanical calibration kit contains precision standard devices to calibrate network analyzers in the N-type interface. This kit also contains adapters to change the sex of the test port, and a torque wrench to ensure a repeatable reliable connection.

Model	Frequency	Spec.	List	qty.
SCKCL03-N(75Ω) (Calibration Level)	DC - 3GHz	Open: $\pm 1.6^\circ$ Short: $\pm 1.2^\circ$ Load: VSWR<1.04 Adaptor: VSWR<1.04	Open: N (M), 75Ω	1
			Open: N (F), 75Ω	1
			Short: N (M), 75Ω	1
			Short: N (F), 75Ω	1
			Load: N (M), 75Ω	1
			Load: N (F), 75Ω	1
			N(f),75Ω-N(f),75Ω adaptor	1
			N(m),75Ω-N(m),75Ω adaptor	1
			N(m),75Ω-N(f),75Ω adaptor	1
			N(f),50Ω-N(m),75Ω adaptor	1
			N(m),50Ω-N(m),75Ω adaptor	1
			N(m),50Ω-N(f),75Ω adaptor	1
			N(f),50Ω-N(f),75Ω adaptor	1
			N-type Torque wrench	1

SCKCL03-N(75Ω) High Precision Calibration Kit

(DC - 3GHz / N-type)

Material Information

Basic Data	
Interface	IEEE Std 287
Mating Cycles	>500 cycles
Coupling Torque	0.9Nm
Open-End Wrench Size	8mm

Electrical Data	
Frequency	DC - 3GHz
Impedance	75Ω
Average Power	≤0.5W

Materials	
Center Conductor	Au-plated Beryllim Copper
Body	Copper Plating / Staineless Stell, Passivated
Connector Nut	Stainless Steel, Passivated

***Note:** Information will conduct the necessary updates , the contents of this document are subject to change without notice*